



SCALE MATT is an innovative coating which has been designed for long-lasting roofing and cladding. The unique finish of V-MATT ensures maximum resistance to scratching giving the surface finish a beautiful crystalline look.

Properties	 10% bigger grain, 10% higher gloss Includes Polyester resin & Melamine hardening system that prolongs the coating durability Improved physical & mechanical properties Excellent color retention 		
Application	Durable coating for external use: constructional sector (roofing tiles, trapezoidal sheets, cladding, fences etc.)		
Description	Thickness	30~35 micron Dual side option	
	Gloss	Gardner 60° / Max 6%	
	Colors	RAL or RR palette (color matching possible upon request)	
	Surface condition	Wrinkle / Big Grain	
	Surface protection	Standard Protective films are usually not suitable for wrinkled surfaces	
Performance	Adhesion of the coating (T-Bend)	2T (no loss of adhesion)	
	Resistance to cracking on bend (T-Bend)	1.5~2T no crack	
	Impact resistance	18J	
	Surface pencil hardness	Н	
	Scratch resistance	≥2 kg	
	Corrosion resistanceSalt spray test / humidityCorrosion resistance category	500 h / 1000 h RC3	
	UV resistance • QUV (UVA + H2O) test (2000 hours) • UV resistance category	ΔE ≤ 3; GR ≥ 60% RUV2	
	Fire behavior classification (EN 13501-1)	A1	
	Highest operation temperature	90°C	
	Resistance to acids and bases	Good	
	Resistance to solvents: Aliphatics and alcohols Ketones Aromatics	GoodLowGood to very good	
	Resistance to mineral oils	Good	
Warranty	Rural / Civil / Industrial Environment	Crack, Peel off	15 years
		Fading, Chalking	15 years